

We BRIGHTEN Your BRANDS



BendLUX

Low-profile, flexible strip lighting

- Bendable in both flat and radial directions
- Easy to mount on back or return of channel letter
- Snappable every 45 mm with jumpers in place for easy flat bends and connections
- Constant Current Technology (CCT)

SPECIFICATIONS

Part number 701960-6WS241

Dimensions L x W x H 610 mm x 8 mm x 3 mm

Viewing angle 120°

LEDs per section 3

Lumens per strip 365

Color temperature (nominal) 6500 K

Minimum radial bend radius 25 mm

Operating temperature -40° C to +70° C

Special features Snappable every 45 mm
Jumpers between sections for easy flat bends
and connections

Power 0.3 W per section, 4.2 W per strip

Efficacy 85 lm/W

Power capacity 12.5 strips per SloanLED 60 W 12 VDC power supply

Fastening Peel-n-stick

Packaging 12 strips per box

Product warranty 5-year limited



BendLUX is covered by patents pending.

SloanLED Headquarters
5725 Olivas Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev A 2016-04-04

 **SloanLED**[®]
Leaders in LED Technology